















































L	Length		COLLEG	CTION:	Crystaligh					
W	Width		Type: Structu Trimmir		suspende polished s full-cut cr	stainless st	teel	pendants i	n various	
Н	Height		Pinning Suspen	s:	sizes and nickel pla galvanize	forms ted rings				
Ø	Diameter		Bulb: Cable: Ceiling		max 60 V transpare polished	V - G9 hald nt PVC+P\	ogen VC - 250 c			
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains									
~110V	110 V	MODEL	D	IMENS	IONS (cm	PA(CKAGE	cm	
~230V	230 V		L	W	Н	kg	L	W	Н	E kg
CE	Product conforms to European Community Directive	ICEBERG								
	Product conforms to GOST R									1.3
	Fixable to ceiling	Iceberg 30	30	30	25	4	45	45	37	13
	Fixable to wall	Iceberg 40	40	40	25	5	55	55	37	15
	Table lamp	Iceberg 50	50	50	25	7	65	65	37	19
	E14 Light bulb	Iceberg 60	60	60	30	10	75	75	42	24
G9	G9 Halogen	Iceberg 70	70	70	30	13	85	85	42	29
G4	G4 Halogen									2.5
LED	LED	Iceberg 80	80	80	35	16	95	95	4/	35
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C € P G G9		w			cm, kg,	P20 for all fitti		
F	Lights are fixable to fiery surface directly		L	7 H	L W	all produ illustratio	ucts supplied ons and desc	with voltage riptions for in	formative pui	quest poses only

L	Length		COLLEC	CTION:	Crystaligh	nt				
W	Width		Type: Structur Trimmin	e:	polished s	ed chande stainless st rystal octag	teel	pendants i	n various	
Н	Height		Pinning: Suspen:	S:	sizes and nickel pla	forms				
Ø	Diameter		Bulb: Cable: Ceiling (max 60 V transpare	V - G9 hald ent PVC+P\ chrome-pl	ogen VC - 250 c			
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains									
~110V	110 V	MODEL	DI	IMENS	IONS (cm	PA(CKAGE	cm	
~230V	230 V		L	W	Н	kg	L	W	Н	E kg
CE	Product conforms to European Community Directive	ICEBERG								
	Product conforms to GOST R									
	Fixable to ceiling	Iceberg 90	90	90	40	19	105	105	52	41
	Fixable to wall	Iceberg 100	100	100	45	26	115	115	57	50
	Table lamp	Iceberg 120	120	120	50	35	135	135	62	65
	E14 Light bulb	Iceberg 140	140	140	55	50	155	155	67	85
G9	G9 Halogen	Iceberg 160	160	160	70	70	175	175	82	120
G4	G4 Halogen									
LED	LED	Iceberg 180	180	180	70	100	195	195	82	156
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V -230V C € P G G9		w	- IH	safety cl units in o	ARKED OTHE lassification IF cm, kg,	P20 for all fitti		
F	Lights are fixable to fiery surface directly		L	7 Н	L W	all produ illustratio	ucts supplied ons and desci	with voltage riptions for in	formative pu	equest Irposes only

L	Length	man had been been	COLLE	CTION:	Crystaligh	nt						
W	Width		Type: Structu Trimmir		suspende polished full-cut cr	stainless s		pendants	in various			
Н	Height		Pinning Suspen	s:	sizes and nickel pla	forms ted rings	- Ø 1,5 mr					
Ø	Diameter		Bulb: Cable: Ceiling		max 60 V transpare	V - G9 hale ent PVC+P		cm				
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains	NACE										
~110V	110 V	MODEL		IMENS	SIONS	cm	PA(CKAGE	: cm	۱		
~230V	230 V		L	W	Н	kg	L	W	Н	S kg		
CE	Product conforms to European Community Directive	ICEBERG DEEP										
PG	Product conforms to GOST R											
	Fixable to ceiling	Iceberg deep 30	30	30	80	4	45	45	92	17		
	Fixable to wall	Iceberg deep 40	40	40	80	12	55	55	92	27		
	Table lamp	Iceberg deep 50	50	50	100	18	65	65	112	38		
	E14 Light bulb	Iceberg deep 60	60	60	100	23	75	75	112	45		
G9	G9 Halogen	50 1										
G4	G4 Halogen											
LED	LED											
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C E P T G 9		w				P20 for all fitt				
F	Lights are fixable to fiery surface directly			7 н	L W	all produ illustrati	ucts supplied ons and desc	with voltage riptions for ir	110V upon re nformative pu	equest rposes only		

L	Length		COLLECTION: Crystalight									
W	Width		Type: Structur Trimmin		suspende polished : full-cut cr	stainless s		pendants i	n various			
Н	Height		sizes and forms Pinnings: nickel plated rings Suspension: galvanized bowden - Ø 1,5 mm Bulb: max 60 W - G9 halogen Cable: transparent PVC+PVC - 250 cm Ceiling Rose: polished chrome-plated steel									
Ø	Diameter	and the second s										
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains											
~110V	110 V	MODEL	DI	IMENS	SIONS	cm	PA(CKAGE	: cm			
~230V	230 V		L	W	Н	kg	L	W	Н	S kg		
CE	Product conforms to European Community Directive	ICEBERG										
PG	Product conforms to GOST R											
<u> </u>	Fixable to ceiling	Iceberg 100/40	100	40	28	13	115	55	40	36		
→	Fixable to wall	Iceberg 20/48	120	48	30	15	135	63	42	43		
	Table lamp	Iceberg 140/56	140	56	32	25	155	71	44	58		
(4)	E14 Light bulb	Iceberg 160/64	160	64	34	35	175	79	46	74		
G9	G9 Halogen	Iceberg 180/72	180	72	36	50	195	87	48	95		
G4	G4 Halogen		200		3.0	4 F	215	0.5	F.0	110		
LED	LED	Iceberg 200/80	200	80	38	65	215	95	50	119		
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C E P G G G G		W		safety c units in	IARKED OTHI lassification IF cm, kg,	20 for all fitt				
F	Lights are fixable to fiery surface directly			' H `	L W	all produ illustrati	ucts supplied ons and desc	with voltage riptions for in	110V upon re formative pu	rposes only		

L	Length		COLLE	CTION:	Crystaligh	nt				
W	Width		Type: Structui Trimmin		polished	ed chande stainless s cystal octa		nendants i	n various	
Н	Height	A Charles To the Control of the Cont	Pinning: Suspen:	S:	sizes and nickel pla	forms ited rings	ı - Ø 1,5 mr			
Ø	Diameter		Bulb: Cable: Ceiling I		max 60 V transpare	V - G9 hale ent PVC+P		:m		
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains									
~110V	110 V	MODEL	D	IMENS	SIONS	cm	PAG	CKAGE	cm	
~230V	230 V		L	W	Н	kg	L	W	Н	S kg
CE	Product conforms to European Community Directive	ICEBERG								
PG	Product conforms to GOST R									122
†	Fixable to ceiling	Iceberg 220/88	220	88	40	75	235	103	52	138
	Fixable to wall	Iceberg 240/96	240	96	42	85	255	111	54	165
	Table lamp									
	E14 Light bulb									
€TI G9	G9 Halogen									
G4	G4 Halogen									
LED	LED									
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C € P G G G		W		units in	1ARKED OTHI lassification If cm, kg,			
F	Lights are fixable to fiery surface directly			' н	L W	all prod illustrati	ucts supplied ons and desc	with voltage riptions for in	110V upon re formative pu	equest Irposes only

L	Length		COLLECTION: Crystalight									
W	Width		Type: Structur Trimmin		suspende polished : full-cut cr	stainless s		pendants i	n various			
Н	Height		sizes and forms Pinnings: nickel plated rings Suspension: galvanized bowden - Ø 1,5 mm Bulb: max 60 W - G9 halogen Cable: transparent PVC+PVC - 250 cm Ceiling Rose: polished chrome-plated steel									
Ø	Diameter											
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains											
~110V	110 V	MODEL	MODEL DIMENS			cm	PA(CKAGE	cm			
~230V	230 V		L	W	Н	kg	L	W	Н	S kg		
CE	Product conforms to European Community Directive	ICEBERG										
P	Product conforms to GOST R											
	Fixable to ceiling	Iceberg 100/25	100	25	22	9	115	40	32	23		
	Fixable to wall	Iceberg 120/30	120	30	24	10	135	45	34	28		
	Table lamp	Iceberg 140/35	140	35	26	12	155	50	36	29		
	E14 Light bulb	Iceberg 160/40	160	40	28	25	175	55	38	48		
G9	G9 Halogen	Iceberg 180/45	180	45	30	40	195	60	40	63		
G4	G4 Halogen		200		2.0		2.15		42	76		
LED	LED	Iceberg 200/50	200	50	32	50	215	65	42	/6		
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C E PG T G9		IW.			IARKED OTHI lassification IF cm, kg,	P20 for all fitt				
F	Lights are fixable to fiery surface directly			' н `	L W	all produ illustration	ucts supplied ons and desc	with voitage riptions for in	formative pu	rposes only		

L	Length		COLLEC	CTION:	Crystaligl	nt						
W	Width	and the state of t	Type: suspended chandelier Structure: polished stainless steel Trimmings: full-cut crystal octagons and pendants in various									
Н	Height		Pinning: Suspen:	S:	sizes and nickel pla	forms ited rings	ı - Ø 1,5 mm					
Ø	Diameter		Bulb: Cable: Ceiling (max 60 V transpare	V - G9 hale ent PVC+P						
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains											
~110V	110 V	MODEL	DI	IMENS	SIONS	cm	PAC	CKAGE	cm			
~230V	230 V		L	W	Н	kg	L	W	Н	E kg		
CE	Product conforms to European Community Directive	ICEBERG										
P	Product conforms to GOST R											
1	Fixable to ceiling	Iceberg 220/55	220	88	34	60	235	70	44	89		
	Fixable to wall	Iceberg 240/60	240	60	36	70	255	75	46	103		
	Table lamp											
	E14 Light bulb											
G9	G9 Halogen											
G4	G4 Halogen											
LED	LED											
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C € P G G G G		W		IF NOT M safety c units in	1ARKED OTHE lassification IF cm, kg,	ERWISE: 20 for all fitt	ings			
F	Lights are fixable to fiery surface directly			' н `	L W	all prod	ucts supplied ons and descr	with voltage riptions for in	110V upon re formative pu	quest rposes only		