













L	Length		СО	LECTIC	N: Crys	talight							
W	Width	Calcium de la Ca	Stru	Type: suspended chandelier Structure: polished stainless steel Trimmings: full-cut crystal octagons and pendants in various									
Н	Height			sizes and forms Pinnings: nickel plated rings Suspension: galvanized bowden - Ø 1,5 mm									
Ø	Diameter	原 如此 病 2000年 1000年 1000年 1	Bul Cab):	max tran	60 W - parent	- G9 hald : PVC+P\		cm				
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains		Cen										
~110V	110 V	MODEL		DIMI	ENSIOI	√S cn	n	PA	CKAGE	cm			
~230V	230 V		L	,	V	1	kg	L	W	Н	S kg		
CE	Product conforms to European Community Directive	KOI											
P	Product conforms to GOST R					•		0.5			22		
	Fixable to ceiling	Koi 80/80	80) {	30 1	8	17	95	95	27	33		
	Fixable to wall	Koi 100/100	10		00	8	21	115	115	27	41		
	Table lamp	Koi 120/120	12		20	8	27	145	145	27	52		
	E14 Light bulb	Koi 140/140	14) I	40	8	32	155	155	27	62		
G9	G9 Halogen	Koi 160/160	16	$\frac{1}{2}$	60	8	37	175	175	27	72		
G4	G4 Halogen	100/100											
LED	LED												
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C E P 1 + G9			w		safety cl units in d	cm, kg,	P20 for all fitt				
F	Lights are fixable to fiery surface directly			L	IH L	W	all produ illustratio	ucts supplied ons and desc	with voltage criptions for in	110V upon re formative pu	equest Irposes only		

L	Length		COLLEG	CTION:	Crystaligl	ht						
W	Width	(A)	Type: Structu Trimmir	re:	polished	ed chande stainless s rystal octa		oendants i	n various			
Н	Height		Pinning Suspen	S:	sizes and nickel pla	forms ated rings						
Ø	Diameter	150 pt 200 500 2 200 pt 200 pt 150 150 150 150 150 150 150 150 150 150	Suspension: galvanized bowden - Ø 1,5 mm Bulb: max 60 W - G9 halogen Cable: transparent PVC+PVC - 250 cm Ceiling Rose: polished chrome-plated steel									
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains											
~110V	110 V	MODEL	D	IMENS	IONS	cm	PA(CKAGE	cm			
~230V	230 V		L	W	Н	kg	L	W	Н	S kg		
CE	Product conforms to European Community Directive	KOI +] +									
PG	Product conforms to GOST R											
<u> </u>	Fixable to ceiling	Koi + 80/80	80	80	22	21	95	95	27	37		
	Fixable to wall	Koi + 100/100	100	100	22	24	115	115	27	45		
	Table lamp	Koi + 120/120	120	120	22	34	145	145	27	56		
	E14 Light bulb	Koi + 140/140	140	140	22	36	155	155	27	67		
G9	G9 Halogen	Koi + 160/160	160	160	22	42	175	175	27	77		
G4	G4 Halogen		100	133		12	173	173				
LED	LED											
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C 6 P T T G 9		w				P20 for all fitt				
F	Lights are fixable to fiery surface directly		L		W	all prodi illustrati	ucts supplied ons and desc	with voltage riptions for in	110V upon re formative pu	equest Irposes only		

L	Length		COLLECTION: Crystalight Type: suspended chandelier Structure: polished stainless steel Trimmings: full-cut crystal octagons and pendants in various								
W	Width	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)									
Н	Height		Pinning Suspen	S:	sizes and nickel pla	forms ated rings	ı - Ø 1,5 mr				
Ø	Diameter		Bulb: Cable: Ceiling		max 60 \ transpare	W - G9 hal ent PVC+P		:m			
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains										
~110V	110 V	MODEL	D	imens	IONS	cm	PA	CKAGE	cm		
~230V	230 V		L	W	Н	kg	L	W	Н	S kg	
CE	Product conforms to European Community Directive	KOI)						
PC	Product conforms to GOST R										
†	Fixable to ceiling	Koi 160/80	160	80	18	27	175	95	27	50	
	Fixable to wall	Koi 180/110	180	110	18	34	195	125	27	65	
	Table lamp	Koi 220/110	220	110	18	39	235	125	27	74	
	E14 Light bulb	Koi 300/110	300	110	18	45	165	125	27	55 2 pcs	
G9	G9 Halogen	Koi 400/110	400	110	18	49	215	125	27	61/	
G4	G4 Halogen	1001 100/110	100	110			213	123		2 pcs	
LED	LED										
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C E P + G9		w			1ARKED OTH :lassification II cm, kg,	P20 for all fitt			
F	Lights are fixable to fiery surface directly				W	all prod illustrati	ucts supplied ons and desc	with voltage riptions for in	110V upon re formative pu	equest urposes only	

L	Length		COLLECTION: Crystalight									
W	Width		Type: Structu Trimmir	re:	polished:	ed chande stainless s rystal octa		pendants ii	n various			
Н	Height		Pinning Suspen	S:	sizes and nickel pla	forms ted rings						
Ø	Diameter	「国際 中国 第2日 東西 (10日本) 10日本 (10日本) (1	Suspension: galvanized bowden - Ø 1,5 mm Bulb: max 60 W - G9 halogen Cable: transparent PVC+PVC - 250 cm Ceiling Rose: polished chrome-plated steel									
+	Chandeliers with + sign: the top of the chandelier is also covered with crystal chains											
~110V	110 V	MODEL DIMENSIONS cm PACKAGE of								m		
~230V	230 V		L	W	Н	kg	L	W	Н	E kg		
CE	Product conforms to European Community Directive	KOI +										
Po	Product conforms to GOST R						<u> </u>					
<u> </u>	Fixable to ceiling	Koi + 160/80	160	80	22	27	175	95	27	54		
	Fixable to wall	Koi + 180/110	180	110	22	34	195	125	27	69		
	Table lamp	Koi + 220/110	220	220	22	43	235	125	27	78		
	E14 Light bulb	Koi + 300/110	300	220	22	50	165	125	27	57 2 pcs		
G9	G9 Halogen	Koi + 400/110	400	110	22	54	215	125	27	63/		
G4	G4 Halogen									2 pcs		
LED	LED											
	Only basic insulation, accesible conductors are earthed. Earthing: compulsory.	~110V ~230V C € P 1 1 1 1 1 1 1 1 1 1		w				20 for all fitti				
F	Lights are fixable to fiery surface directly		L	IH	W		ucts supplied ons and descr					